

	<b>Combs Unified School District, #44</b> Amendment #2		301 E. Combs Road San Tan Valley, AZ 85140
	IFB: 18-02-18 <b>PROJECT: Roof Restoration and Weatherization at Jack Harmon Elementary</b>	Page 1 of 1	

March 29, 2018

This Amendment is released to all interested parties.

1. Modification of Technical Specifications:

A. Elastomeric Coating, GAF United Coatings Aquathon

**TECHNICAL SPECIFICATIONS:**

**SECTION 09 96 53 – ELASTOMERIC COATINGS**

A. Reference Page 5, Article 2.3 MATERIALS, Paragraph B.2 Performance Requirements:

Revision: Item a. Revise text “15 mils” to “26 mils”

B. Reference Page 9, Article 3.4 ELASTOMERIC COATING APPLICATION, Paragraph D:

Revision: Revise the paragraph to read as follows:

“D. The entire wall surface shall receive AQUATHON advanced acrylic elastomer coating applied as follows:

For issuance of a 10-year waterproofing warranty, two or three separate coats of fluid-applied waterproofing shall be applied at a nominal total thickness of 26 dry mils (483 microns) to meet manufacturer’s latest warranty requirements.

The following estimated coverage rates should be used as a guide in figuring fluid-applied waterproofing material requirements for 10 year warranty:

<b>Substrate</b>	<b>Gallons/100 sq. ft.</b>
<b>10-Year Warranty</b>	
Concrete (smooth)	2.6 (1.4 l/m <sup>2</sup> ) in 2 coats
Concrete Block, Brick	3.2 (1.3 l/m <sup>2</sup> ) in 2 coats
Lightweight Pumice Block	3.8 (1.5 l/m <sup>2</sup> ) in 2 or 3 coats
Split Face, Stucco or Coarse Textured Surfaces”	4.4(1.8 l/m <sup>2</sup> ) in 3 coats

2. Gaco Substitution Request is pending.
3. Remember to sign your offer sheet and acknowledge this amendment.
4. All other terms and conditions remain the same.
5. End of Amendment #2.