



## **Oak Grove School District**

# **Control of Hazardous Energy Program (Lockout/Tagout)**



## **The Control of Hazardous Energy (Lockout/Tagout) Program**

**1910.147**

**The following lockout/tagout program is provided to assist employees in complying with the requirements of 29 CFR 1910.147, as well as to provide other helpful information.**

**1910.147**  
**The Control of Hazardous Energy (Lockout/Tagout) Procedure**  
**Table of Contents**

- I. Objective
  
- II. Assignment of Responsibility
  
- III. Procedures
  - A. Preparation for Lockout or Tagout
  - B. Electrical
  - C. Hydraulic/Pneumatic
  - D. Fluids and Gases
  - E. Mechanical Energy
  - F. Release from Lockout/Tagout
  - G. Service or Maintenance Involving More than One Person
  - H. Removal of an Authorized Employee's Lockout/Tagout by the Company
  - I. Shift or Personnel Changes
  - J. Procedures for Outside Personnel/Contractors
  - K. Training and Communication
  - L. Periodic Inspection



## Oak Grove School District

### Lockout/Tagout Procedure

#### I. OBJECTIVE

The objective of this procedure is to establish a means of positive control to prevent the accidental starting or activating of machinery or systems while they are being repaired, cleaned and/or serviced. This program serves to:

- A. Establish a safe and positive means of shutting down machinery, equipment and systems.
- B. Prohibit unauthorized personnel or remote control systems from starting machinery or equipment while it is being serviced.
- C. Provide a secondary control system (tagout) when it is impossible to positively lockout the machinery or equipment.
- D. Establish responsibility for implementing and controlling lockout/tagout procedures.
- E. Ensure that only approved locks, standardized tags and fastening devices provided by the company will be utilized in the lockout/tagout procedures.

#### II. ASSIGNMENT OF RESPONSIBILITY

- A. Fred Dickey will be responsible for implementing the lockout/tagout program.
- B. Anthony Valdez and Fred Dickey are responsible for enforcing the program and insuring compliance with the procedures in their departments.
- C. Fred Dickey will conduct the annual inspection and certification of the authorized employees.
- D. Authorized employees (those listed in Attachment A) are responsible for following established lockout/tagout procedures. An authorized employee is defined as a person who locks out or tags out machines or equipment in order to perform servicing or maintenance on that machine or equipment. An affected employee becomes an authorized employee when that employee's duties include performing servicing or maintenance covered under 1910.147, The Control of Hazardous Energy (lockout/tagout).
- E. Affected employees (all other employees in the facility) are responsible for insuring they do not attempt to restart or re-energize machines or equipment that are locked out or tagged out. An affected employee is defined as a person whose job requires him/her to operate or use a machine or equipment on which servicing or maintenance is being performed under lockout or tagout, or whose job requires him/her to work in an area in which such servicing or maintenance is being performed.

#### III. PROCEDURES

The ensuing items are to be followed to ensure both compliance with the OSHA Control of Hazardous Energy Standard and the safety of our employees.

### **A. Preparation for Lockout or Tagout**

Employees who are required to utilize the lockout/tagout procedure, must be knowledgeable of the different energy sources and the proper sequence of shutting off or disconnecting energy means. The four types of energy sources are:

1. electrical (most common form);
2. hydraulic or pneumatic;
3. fluids and gases; and
4. mechanical (including gravity).

More than one energy source may be utilized on some equipment and the proper procedure must be followed in order to identify energy sources and lockout/tagout accordingly.

### **B. Electrical**

1. Shut off power at machine and disconnect.
2. Disconnecting means must be locked or tagged.
3. Press start button to see that correct systems are locked out.
4. All controls must be returned to their safest position.
5. Points to remember:
  - a. If a machine or piece of equipment contains capacitors, they must be drained of stored energy.
  - b. Possible disconnecting means include the power cord, power panels (look for primary and secondary voltage), breakers, the operator's station, motor circuit, relays, limit switches, and electrical interlocks.
  - c. Some equipment may have a motor isolating shut-off and a control isolating shut-off.
  - d. If the electrical energy is disconnected by simply unplugging the power cord, the cord must be kept under the control of the authorized employee or the plug end of the cord must be locked out or tagged out.

### **C. Hydraulic/Pneumatic**

1. Shut off all energy sources (pumps and compressors). If the pumps and compressors supply energy to more than one piece of equipment, lockout or tagout the valve supplying energy to the piece of equipment being serviced.
2. Stored pressure from hydraulic/pneumatic lines shall be drained/bled when release of stored energy could cause injury to employees.
3. Make sure controls are returned to their safest position (off, stop, standby, inch, jog, etc.).

### **D. Fluids and Gases**

1. Identify the type of fluid or gas and the necessary personal protective equipment.
2. Close valves to prevent flow, and lockout/tagout.
3. Determine the isolating device, then close and lockout/tagout.
4. Drain and bleed lines to zero energy state.
5. Some systems may have electrically controlled valves. If so, they must be shut off and locked/tagged out.
6. Check for zero energy state at the equipment.

### **E. Mechanical Energy**

Mechanical energy includes gravity activation, energy stored in springs, etc.

1. Block out or use die ram safety chain.
2. Lockout or tagout safety device.
3. Shut off, lockout or tagout electrical system.
4. Check for zero energy state.
5. Return controls to safest position.

### **F. Release from Lockout/Tagout**

1. Inspection: Make certain the work is completed and inventory the tools and equipment that were used.
2. Clean-up: Remove all towels, rags, work-aids, etc.
3. Replace guards: Replace all guards possible. Sometimes a particular guard may have to be left off until the start sequence is over due to possible adjustments. However, all other guards should be put back into place.
4. Check controls: All controls should be in their safest position.
5. The work area shall be checked to ensure that all employees have been safely positioned or removed and notified that the lockout/tagout devices are being removed.
6. Remove locks/tags. Remove only your lock or tag.

### **G. Service or Maintenance Involving More than One Person**

When servicing and/or maintenance is performed by more than one person, each authorized employee shall place his own lock or tag on the energy isolating source. This shall be done by utilizing a multiple lock scissors clamp if the equipment is capable of being locked out. If the equipment cannot be locked out, then each authorized employee must place his tag on the equipment.

### **H. Removal of an Authorized Employee's Lockout/Tagout by Oak Grove School District**

Each location must follow the written emergency procedures that comply with 1910.147(e)(3) to be utilized at that location. Emergency procedures for removing lockout/tagout should include the following:

1. Verification by employer that the authorized employee who applied the device is not in the facility.
2. Make reasonable efforts to advise the employee that his/her device has been removed. (This can be done when he/she returns to the facility).
3. Ensure that the authorized employee has this knowledge before he/she resumes work at the facility.

#### **I. Shift or Personnel Changes**

Each facility must follow the written procedures based on specific needs and capabilities. Each procedure must specify how the continuity of lockout or tagout protection will be ensured at all times. See 1910.147(f)(4).

#### **J. Procedures for Outside Personnel/Contractors**

Outside personnel/contractors shall be advised that Oak Grove School District has and enforces the use of lockout/tagout procedures. They will be informed of the use of locks and tags and notified about the prohibition of attempts to restart or re-energize machines or equipment that are locked out or tagged out.

The Oak Grove School District will obtain information from the outside personnel/contractor about their lockout/tagout procedures and advise affected employees of this information.

The outside personnel/contractor will be required to sign a certification form.

#### **K. Training and Communication**

Each authorized employee who will be utilizing the lockout/tagout procedure will be trained in the recognition of applicable hazardous energy sources, type and magnitude of energy available in the work place, and the methods and means necessary for energy isolation and control.

Each affected employee (all employees other than authorized employees utilizing the lockout/tagout procedure) shall be instructed in the purpose and use of the lockout/tagout procedure, and the prohibition of attempts to restart or re-energize machines or equipment that are locked out or tagged out.

Training will be certified using a sign off form. The certifications will be retained in the employee personnel files.

#### **L. Periodic Inspection**

A periodic inspection (at least annually) will be conducted of each authorized employee under the lockout/tagout procedure. This inspection shall be performed by Fred Dickey. If Fred Dickey is also using the energy control procedure being inspected, then the inspection shall be performed by another party.

The inspection will include a review between the inspector and each authorized employee of that employee's responsibilities under the energy control (lockout/tagout) procedure. The inspection will also consist of a physical inspection of the authorized employee while performing work under the procedures.

Fred Dickey shall certify in writing that the inspection has been performed.

*Lock Out-Tag Out procedures approved by the Safety Committee on January 27, 2015. The plan was reviewed and updated August 2015, July 2016 and August 2017.*